

HYDROSTATION

NEW

High efficiency pressurisation unit with integrated inverter


Product compliant with DM 174/2004
(drinking water use)

Compact dimensions

High efficiency

Silent

Easy maintenance


ACCESSORIES

- **Manifolds kit**
Connect two Hydrostation and double the duty
- **Bluetooth module**

TECHNICAL DATA

Max. working pressure	6 bar
Max. liquid temperature	+5°C ÷ +45°C
Max. ambient temperature	+5°C ÷ +50°C
Max. suction depth	6 m
Poles	6
Protection degree	IP65
Connections	GF 1"
Voltage	Single-phase 1~220-240V ±15%

MATERIALS

Cover	Nylon PA6 GF 30%
Impeller and diffuser	PPO + GF 20%
Shaft	Stainless steel AISI 304 (EN 1.4301)
Mechanical seal	Graphite/Silicon Carbide/EPDM



REMOTE CONTROL

Thanks to the Bluetooth® connection, you can control your system remotely, conveniently and intuitively via the Hydrostation app. Download it from the App Store or Google Play.



Single phase 220-240V

6 poles

Model	Code	Euro	HP	kW	Q=Flow rate												Abs. Curr. [A] 230V	DNA	DNM	Weight [kg]
					l/min	0	10	20	30	40	50	60	70	80	90	95				
					m³/h	0	0,6	1,2	1,8	2,4	3	3,6	4,2	4,8	5,4	5,7				
					H=Total head [m]															
HYDROSTATION	1545550000	970.00	1,1	0,8		60	58,5	56	50	43	36	30	25	20	15	5	4,6	G1"	G1"	13,5
HYDROSTATION Bluetooth	1545550001	990.00	1,1	0,8		60	58,5	56	50	43	36	30	25	20	15	5	4,6	G1"	G1"	13,5

HYDROSTATION - Manifolds kit



Model	Code	Euro
HYDRO-TWIN	362331065	500,00

HYDROSTATION - Bluetooth module

Model	Code	Euro
Bluetooth module	362331069	80,00